

**MATTEI ROTARY VANE AIR COMPRESSOR DATA SHEET - FIXED-SPEED**


Model Number:	<b>RVX 90 LX_IE3</b>			Date:	<b>5-May-2022</b>
Cooling Media:	Air-cooled <input checked="" type="checkbox"/>	Water-cooled <input type="checkbox"/>	Oil Injection	<input checked="" type="checkbox"/>	
Inlet Control Scheme:	Load/No Load <input checked="" type="checkbox"/>	Modulation <input type="checkbox"/>	Inverter	<input checked="" type="checkbox"/>	
Starting System:	Full Voltage <input type="checkbox"/>	Star-Delta <input type="checkbox"/>	Soft-Start	<input type="checkbox"/>	

**PERFORMANCE SPECIFICATIONS: SPEED, POWER, PRESSURE**

Compression Module Rotational Speed	<b>1600</b>	rpm
Nominal Drive Motor Rotational Speed	<b>1800</b>	rpm
Drive Motor Nominal Rating	<b>125</b>	hp
Drive Motor Nominal Efficiency	<b>95.2</b>	percent
Maximum Full Flow Operating Pressure <sup>c</sup>	<b>102</b>	psig <sup>c</sup>
Full Load Operating Pressure <sup>b</sup>	<b>123</b>	psig <sup>b</sup>
Fan Motor Nominal Rating (if applicable)	<b>5.0</b>	hp
Fan Motor Nominal Efficiency	<b>n/a</b>	percent

**"VANE GAIN" PERFORMANCE EFFICIENCY GAINS OVER TIME<sup>g</sup>**

Efficiency Improvement timeline	<b>0</b>	<b>500</b>		hours
Rated Capacity at Full Load Operating Pressure <sup>a</sup>	<b>548.1</b>	<b>553.4</b>		acfm <sup>a</sup>
Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	<b>98.87</b>	<b>95.95</b>		kW <sup>d</sup>
Specific Package Input Power at Rated Capacity and Full Load Operating Pressure	<b>18.0</b>	<b>17.3</b>		kW/100 cfm
Isentropic Efficiency at Rated Capacity and Full Load Operating Pressure <sup>f</sup>	<b>74.80</b>	<b>77.80</b>		Percent of ideal compression
Total Package Input Power at Zero Flow	<b>14.70</b>	<b>14.20</b>		Kw



**NOTES:**

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Rated Capacity and Total Package Input Power Energy Consumption at Rated Capacity and Full Load Operating Pressure were measured.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with inlet control scheme.
- Isentropic Efficiency: real performance at flow and pressure per ISO 1217 compared to an ideal compression process.
- VANE GAIN: Proven efficiency and output performance gains as the blades season through normal operation.

**MATTEI ROTARY VANE AIR COMPRESSOR DATA SHEET - FIXED-SPEED**


Model Number:	<b>RVX 90 LX_IE3</b>	Date:	<b>5-May-2022</b>
Cooling Media:	Air-cooled <input checked="" type="checkbox"/>	Water-cooled <input type="checkbox"/>	Oil Injection <input checked="" type="checkbox"/>
Inlet Control Scheme:	Load/No Load <input checked="" type="checkbox"/>	Modulation <input type="checkbox"/>	Inverter <input checked="" type="checkbox"/>
Starting System:	Full Voltage <input type="checkbox"/>	Star-Delta <input type="checkbox"/>	Soft-Start <input type="checkbox"/>

**PERFORMANCE SPECIFICATIONS: SPEED, POWER, PRESSURE**

Compression Module Rotational Speed	<b>1600</b>	rpm
Nominal Drive Motor Rotational Speed	<b>1800</b>	rpm
Drive Motor Nominal Rating	<b>125</b>	hp
Drive Motor Nominal Efficiency	<b>95.2</b>	percent
Maximum Full Flow Operating Pressure <sup>c</sup>	<b>108</b>	psig <sup>c</sup>
Full Load Operating Pressure <sup>b</sup>	<b>123</b>	psig <sup>b</sup>
Fan Motor Nominal Rating (if applicable)	<b>5.0</b>	hp
Fan Motor Nominal Efficiency	<b>n/a</b>	percent

**"VANE GAIN" PERFORMANCE EFFICIENCY GAINS OVER TIME<sup>g</sup>**

Efficiency Improvement timeline	<b>0</b>	<b>500</b>		hours
Rated Capacity at Full Load Operating Pressure <sup>a</sup>	<b>545.6</b>	<b>551.3</b>		acfm <sup>a</sup>
Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	<b>102.16</b>	<b>99.15</b>		kW <sup>d</sup>
Specific Package Input Power at Rated Capacity and Full Load Operating Pressure	<b>18.7</b>	<b>18.0</b>		kW/100 cfm
Isentropic Efficiency at Rated Capacity and Full Load Operating Pressure <sup>f</sup>	<b>74.80</b>	<b>77.80</b>		Percent of ideal compression
Total Package Input Power at Zero Flow	<b>14.70</b>	<b>14.20</b>		Kw



**NOTES:**

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Rated Capacity and Total Package Input Power Energy Consumption at Rated Capacity and Full Load Operating Pressure were measured.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with inlet control scheme.
- Isentropic Efficiency: real performance at flow and pressure per ISO 1217 compared to an ideal compression process.
- VANE GAIN: Proven efficiency and output performance gains as the blades season through normal operation.

**MATTEI ROTARY VANE AIR COMPRESSOR DATA SHEET - FIXED-SPEED**


Model Number:	<b>RVX 90 LX_IE3</b>	Date:	<b>5-May-2022</b>
Cooling Media:	Air-cooled <input checked="" type="checkbox"/>	Water-cooled <input type="checkbox"/>	Oil Injection <input checked="" type="checkbox"/>
Inlet Control Scheme:	Load/No Load <input checked="" type="checkbox"/>	Modulation <input type="checkbox"/>	Inverter <input checked="" type="checkbox"/>
Starting System:	Full Voltage <input type="checkbox"/>	Star-Delta <input type="checkbox"/>	Soft-Start <input type="checkbox"/>

**PERFORMANCE SPECIFICATIONS: SPEED, POWER, PRESSURE**

Compression Module Rotational Speed	<b>1600</b>	rpm
Nominal Drive Motor Rotational Speed	<b>1800</b>	rpm
Drive Motor Nominal Rating	<b>125</b>	hp
Drive Motor Nominal Efficiency	<b>95.2</b>	percent
Maximum Full Flow Operating Pressure <sup>c</sup>	<b>116</b>	psig <sup>c</sup>
Full Load Operating Pressure <sup>b</sup>	<b>123</b>	psig <sup>b</sup>
Fan Motor Nominal Rating (if applicable)	<b>5.0</b>	hp
Fan Motor Nominal Efficiency	<b>n/a</b>	percent

**"VANE GAIN" PERFORMANCE EFFICIENCY GAINS OVER TIME<sup>g</sup>**

Efficiency Improvement timeline	<b>0</b>	<b>500</b>		hours
Rated Capacity at Full Load Operating Pressure <sup>a</sup>	<b>543.5</b>	<b>549.1</b>		acfm <sup>a</sup>
Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	<b>105.45</b>	<b>102.34</b>		kW <sup>d</sup>
Specific Package Input Power at Rated Capacity and Full Load Operating Pressure	<b>19.4</b>	<b>18.6</b>		kW/100 cfm
Isentropic Efficiency at Rated Capacity and Full Load Operating Pressure <sup>f</sup>	<b>74.80</b>	<b>77.80</b>		Percent of ideal compression
Total Package Input Power at Zero Flow	<b>14.70</b>	<b>14.20</b>		Kw



**NOTES:**

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Rated Capacity and Total Package Input Power Energy Consumption at Rated Capacity and Full Load Operating Pressure were measured.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with inlet control scheme.
- Isentropic Efficiency: real performance at flow and pressure per ISO 1217 compared to an ideal compression process.
- VANE GAIN: Proven efficiency and output performance gains as the blades season through normal operation.

