COMPRESSOR DATA SHEET

Rotary Vane Compressor: Fixed Speed

| MODEL DATA - FOR COMPRESSED AIR | | | |
|---------------------------------|---|--------------|-------------------|
| 1 | Manufacturer: Mattei Compressors, II | nc. | |
| | Model Number: AC 45 HX | Date: | Oct-16 |
| 2 | X Air-cooled Water-cooled | Type: | Vane |
| | X Oil-injected Oil-free | # of Stages: | 1 |
| | Rated Capacity at Full Load Operating | | |
| 3 | Pressure ^a | 302.7 | acfm ^a |
| 4 | Full Load Operating Pressure b | 131 | psig b |
| 5 | Maximum Full Flow Operating Pressure c | 145 | psig c |
| 6 | Drive Motor Nominal Rating | 60 | hp |
| 7 | Drive Motor Nominal Efficiency | 95.0 | percent |
| 8 | Fan Motor Nominal Rating (if applicable) | 1.48 | hp |
| 9 | Fan Motor Nominal Efficiency | 86.0 | percent |
| 10 | Total Package Input Power at Zero Flow | 11.70 | Kw |
| 11 | Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d | 65.28 | kW^d |
| 12 | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure | 21.57 | kW/100 cfm |

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
 b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured
- for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
 d. Total package input power at other than reported operating points will vary with control strategy.

